



GLIDDEN TRADE CONTRACT SILK

G219

PRODUCT INFORMATION

Typical Use	Glidden Trade Contract Silk is a professional quality, high opacity, quick drying silk emulsion for both old and new surface areas. Suitable for all normal interior wall and ceiling surfaces. Before preparing any surface for painting, read the Health Safety & Environmental information on page 2 about old lead-based paints.
Codes according to the List of Wastes Regulations	Product as supplied: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11. Part-used containers, containing dried residues of the supplied product: Assigned as non-hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11 Used containers, rigorously scraped out and containing dried residues of the supplied product: Assigned as non-hazardous waste code 15 01 02 plastic packaging OR non-hazardous waste code 15 01 04 metal packaging. "Rigorously scraped out" means removing the maximum amount of product from the container by physical or mechanical means (draining or scraping) to leave a residue or contamination that cannot be removed by such means. These codes have been assigned based on the actual composition of the product both as supplied and as dried residues. If mixed with other wastes, the waste codes quoted may not be applicable.
Pack Size	10 and 15 litre only. Not all colours are available in both pack sizes.
Colour Range	See Glidden Trade Colour Card.
Film Properties	Chemical Resistance: Not suitable. Heat Resistance: Not suitable for use on heated surfaces eg radiators. Water Resistance: Will tolerate the levels of atmospheric humidity present in normal interior environments.
Composition (nominal)	Pigment: Lightfast Non-Lead Pigments. Binder: Acrylic Copolymer Emulsion. Solvent: Water.
Volume Solids	25%
Application Method	Brush, roller or spray.
Drying Times	<i>Single coat at standard thickness:</i> Touch Dry: Dependent upon temperature and humidity. Recoat: 2-4 hours.
Practical Coverage	A guide to the practical coverage which can be achieved under normal conditions is up to 14m ² / litre.
Thinning	Sealing new or bare surfaces: Add up to 1 part clean water to 10 parts paint. Normal use: Thinning is not required. Conventional spray application: Add up to 1 part clean water to 5 parts paint. Airless spray application: Thinning is not required.
Spray Recommendations	Conventional Spray: Satisfactory through most equipment. Airless Spray: A typical recommendation for airless spray application is a minimum working pressure on paint of 140 kg/cm ² (2000 lb/sq in) with a Spray Tip size of 0.38mm (15 thou) Spray Tip Angle 65°
Cleaning Up	After use, remove as much paint as possible from equipment before cleaning with clean water.

Do not use or store in extremes of temperature and protect from frost.

SURFACE PREPARATION

Surfaces must be sound, clean, dry and free from all defective or poorly adhering material, dirt, grease and salts. New plaster and masonry must be fully dry before priming.

SYSTEM INFORMATION

Stir thoroughly before use.

On very absorbent surfaces apply a sealing coat of thinned Glidden Trade Contract Silk.

Finishing:

Apply 1 or 2 coats of Glidden Trade Contract Silk.

HEALTH, SAFETY & ENVIRONMENTAL INFORMATION

WATER-BASED PAINT

Ensure good ventilation during application and drying.

Do not breathe spray. When spraying inside, wearing a cartridge mask of Assigned Protection Factor 40 x OEL for particulates is recommended.

Avoid contact with skin and eyes. When applying it is advisable to wear eye protection.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.

After contact with skin, wash immediately with plenty of soap and water or a proprietary skin cleanser. Do not use solvent, thinners or white spirit.

Keep out of the reach of children.

If swallowed, seek medical advice immediately and show this container or label.

Do not use or store by hanging on a hook.

Do not empty into drains or watercourses.

Safety data sheet available for professional user on request.

Avoid the inhalation of dust. Wear a suitable face mask if dry sanding.

Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead. For further advice contact ICI Paints/AkzoNobel, Wexham Road, Slough SL2 5DS.

Tel: 08444 817 818

EU limit value for this product (cat A/b) : 150g/l (2007) / 100g/l (2010)

This product contains max. 20g/l VOC

See www.glidden.co.uk

VOC Content Low 0.30% - 7.99%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

Dulux Trade, Glidden Oval and the ICI Roundel are trademarks of AkzoNobel.

© AkzoNobel 2010 (05112010 SDSG219IT)

